

Stability, Precision, Flexibility

TwinLoop Anchor



Stability, Precision, Flexibility

PEEK TwinLoop Anchor

The PEEK TwinLoop Anchor is named for its unique double-looped suture eyelets. The Suture Eyelet (SE) versions are offered with one or two strands of Force Fiber. A third configuration offers one strand of working suture threaded through the body of the anchor.

The anchor body is seated firmly onto the distal tip of the inserter for stability and rigidity upon insertion. The inserter is fully cannulated to house the working suture, which is neatly wound on the back of the handle for ease of use.

The body of the PEEK TwinLoop Anchor is 2.5mm and features 1mm barbs for optimized fixation. The overall size of the anchor is 3.5mm, excellent for SLAP/Bankart procedures.



PEEK TwinLoop Anchor
with One Strand of Force Fiber
3910-400-035

PEEK TwinLoop
Anchor Suture Eyelet (SE)
with One Strand of Force Fiber
3910-400-135

PEEK TwinLoop
Anchor Suture Eyelet (SE)
with Two Strands of Force Fiber
3910-400-235

Features:

Two suture eyelets for flexibility and suture management.

Three configurations for versatility. Anchor body is rigidly attached to inserter.

Easy to disassemble inserter handle.



PEEK TwinLoop Anchor with
One Strand of Force Fiber
3910-400-035



PEEK TwinLoop Anchor Suture Eyelet (SE)
with One Strand of Force Fiber
3910-400-135



PEEK TwinLoop Anchor Suture Eyelet (SE)
with Two Strands of Force Fiber
3910-400-235

PEEK TwinLoop Instrumentation

The instrumentation for the PEEK TwinLoop Anchor was designed for ease of use. The large handle guide provides better grip and ergonomics. The angle on the proximal end of the spiral drill seats into the guide when the required depth is reached. The spade drill features a shoulder on the distal end to stop the guide at the appropriate depth.

Once the anchor has been inserted into the drill hole and the suture unwound from the inserter, the large handle guide and inserter may be removed as one.

Features:

Large handle guide for better grip and ergonomics.

Hard stops on drills and anchor for more precise depths.

Laser marks on the window of the guide that line up with the laser marks on inserter shaft for easy confirmation of anchor depth.



TwinLoop Spiral Drill
3910-400-005



TwinLoop Spade Tip Drill
3910-400-001



TwinLoop Awl
3910-400-002



TwinLoop Obturator
3910-400-003

TwinLoop Guide
3910-400-000





Joint Replacements

Trauma, Extremities & Deformities

Craniomaxillofacial

Spine

Biologics

Surgical Products

Neuro & ENT

Interventional Pain

Navigation

Endoscopy

Communications

Imaging

Patient Handling Equipment

EMS Equipment

325 Corporate Drive
Mahwah, NJ 07430
t: 201 831 5000

www.stryker.com

A surgeon should always rely on his or her own professional clinical judgment when deciding to use which products and/or techniques on individual patients. Stryker is not dispensing medical advice and recommends that surgeons be trained in orthopaedic surgeries before performing any surgeries.

The information presented is intended to demonstrate the breadth of Stryker product offerings. Always refer to the package insert, product label and/or user instructions before using any Stryker product. Products may not be available in all markets. Product availability is subject to the regulatory or medical practices that govern individual markets. Please contact your Stryker representative if you have questions about the availability of Stryker products in your area.

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: PEEK, Stryker, Twinloop. All other trademarks are trademarks of their respective owners or holders.

Literature Number: 1000-900-578D Rev.1
MS/GS 6/08

Copyright © 2008 Stryker
Printed in USA